



KO Series

Variable Capacity Forkliftable and Tippable Tanks

Volume	Diameter (mm)	Height (mm)	Order Code
380L	1000	653	SP-KO-100-0380
550L	1000	903	SP-KO-100-0550
750L	1000	1153	SP-KO-100-0750
1050L	1200	1153	SP-KO-100-1050
1350L	1200	1453	SP-KO-120-1350
1600L	1200	1653	SP-KO-120-1600
2500L	1400	1900	SP-KO-140-2500

Standard Equipment

AISI 304 stainless steel casing and bottom with marbled outside, open top with 42mm strengthening rim and flat tank bottom. Secure welded in lifting braces for forklifting and tipping. Standard tyne channel guides 114 x 54mm. Wide tyne channel guides 140 x 100mm.


Floating Lid



AISI 304, with white rubber seal for greater protection, pump and pressure gauge. Additional rubber seals optional.

Optional Accessories *(additional charges apply)*

1.5" or 2" Butterfly & Ball Valves



Unmounted, AISI 304, include end position lock, blind cap and chain.

1.5" or 2" Welded Gland



Mounted, AISI 304, 1.5" or 2" Tri-Clover, or RJT.

Double Jacket for Heating & Cooling

Laser welded onto the tank casing.

Manhole/Mashdoor

Manhole seamlessly moulded out of tank shell 420 x 320mm (LxW). Mashdoor at the bottom with outwards opening door 310 x 420mm (WxH).

