

# Product Information FO Series



## TANK SIZE OPTIONS

Order Code	Volume	Diameter (mm)	Height (mm)
SP-FO-100-1100	<b>1100L</b>	1000	2216
SP-FO-120-1600	<b>1600L</b>	1200	2356
SP-FO-140-2200	<b>2200L</b>	1400	2391
SP-FO-140-3300	<b>3300L</b>	1400	3129
SP-FO-160-2850	<b>2850L</b>	1600	2513
SP-FO-160-3850	<b>3850L</b>	1600	3001
SP-FO-160-4800	<b>4800L</b>	1600	3501
SP-FO-160-5800	<b>5800L</b>	1600	4001
SP-FO-180-3700	<b>3700L</b>	1800	2558
SP-FO-180-4900	<b>4900L</b>	1800	3046
SP-FO-180-6100	<b>6100L</b>	1800	3546
SP-FO-200-4500	<b>4500L</b>	2000	2613
SP-FO-200-6000	<b>6000L</b>	2000	3101



### FO STANDARD EQUIPMENT

AISI 304 stainless steel casing and bottom with marbled outside, strengthening rim and litre scale on outside. Standard round tank shape, self supporting with 3 welded on feet with statically optimised hooped casing. Width of strengthening rim 17mm (up to 300L capacity); 42mm for 520L capacity and up.

**Racking Outlet** Reinforcing plate with 48mm diameter drilled hole for holding 1.5" and 2" welded gland Tri-Clover or RJT.

**Bottom Outlet** Vaulted stable tank bottom with moulded-on forward incline for complete discharge. Moulded-on connection neck, anti-suction with bottom outlet neck as follows:

- Up to 820mm diameter tank (1.5") welded gland Tri-Clover or RJT.
- From 1000mm diameter tank outlet neck (2") welded gland Tri-Clover or RJT.


**Floating Lid** High quality AISI 304 stainless steel floating lid with air seal pump and pressure gauge. Also available with AISI 316 stainless steel at special request (additional charges apply).

### ACCESSORIES *(additional charges apply)*



#### Double Jacket for Heating & Cooling

For temperature regulation, the double jacket is laser welded onto the cylindrical tank casing designed for a working pressure of 2.5 to 6 bar. Connections are 1" AG G threads (BSP). Adaptable on request.



#### Crane & Cable

Includes complete idler set for easy lifting of the floating lid.



#### Crane & Hand Winch

Pulley system with easy winding crank handle attached to tank.

## Kauri Winemaking Innovation

**NZ Tel:** 0800 KAURIWINE  
**NZ Fax:** 04 910 7415

**Aus Tel:** 1800 127 611  
**Aus Fax:** 1800 127 609

**Email:** [info@kauriwine.com](mailto:info@kauriwine.com)  
**Website:** [www.kauriwine.com](http://www.kauriwine.com)

